

Used 18,000 Gallon Storage Vessel

Available for Immediate Delivery LPG/NGL Service

This tank is located in Rocky Mount, NC

If we do not have a new or used tank or set of matching storage vessels in inventory to suit your needs, we will gladly locate the tanks you need at a competitive price, or we can **custom manufacture the tank** or set of vessels you require—to your exact specifications.

Year	MFG	Capacity	PSI	Serial No. / National Board No.	U1A Data Report
1973	Trinity	18,000	250	386971 / 61304	Available





Need help with your project? Save time and money, TransTech can provide Valve & Instrumentation kit to fit your tank, freight to the project site and full installation. Feel comfortable your project will be installed to the latest NFPA 58 Standard and will fit your needs.

Tank Set & Installation! From providing expert engineering assistance in specifying the correct valve and instrumentation, size piers to coordination of freight and offloading - through to site excavation and tank set, we provide a turnkey bulk plant or terminal solution.



TransTech Energy LLC - Tel: (+1)888-206-4563 www.transtechenergy.com

	Arternation P		Chine C	a and the second	THE REAL PROPERTY.	1. R 600009
1. Menulactured by	Trinity I	ndustria	, inc.	P. U. Box 1525	Rocky No	unt,N. C.
2. Manufactured for	E. Sam Die	k Co.	800 N.W. 1		tle, Washingt	on 981.07
a Typeris.		386071		A State No. Not'l.	No. 61.30/1	Yr. Bullt 1973
4. SHELL: Mat'I SA -5	15-70 T.8.7	0,000 ger		Allow O In Dian		0.4. Longen 41 1. 2.25 in.
Welded, Doly Bin	bl. Butt H.T.	No Ives or No No	A.T. Com	Complete) (Yes or) P. Sectioned No	Efficiency 10	1 der ferten ar
6. HEADS: (a) Material		-B	73,000 (b)	Meterial_SA-	155-8	T.S. 73,000
(Ton, boltom, ands (a)End (b)End	.11201	Redius	Knuckle Radius	Extiplical Conic Ratio Apex a	1010 52" I.S. 52" I.S.	Diameter (Convex or Conceye) Conceye
If removable, bolts used	AMateri	al, Spec. No., 1	.s., Size, Number	Other fasts	ming (Desc	ribe of Atlach Sectors)
7. Constructed for max. allowable working pr	250	et max, temp.	125	Min. temp. (when	*F. Corgbine	Top Centerline
8. SAFETY OR RELIE	F VALVE OUTLE	TS: Number_	5	Bire 2"	Loastion She	11 Top Centerline
Purpose, (inter Outlet, Drain)	Number D	lem. or Size	Туря	Mataria	Thickness M	forcement How Interfect Attached
Lig. Out	2	3"	Cplg.	F.S.	6000#	Welded
Fill, Vapor		2.5"	Boch. Cplg.	<u> </u>	Adapter	Welded Welded
Roto		11	Cplg.		3000#	Welded
Thermo.	1	. 1511	Pipe	SA-53-B	XX Hyy	Welded
P.Q. Lal.	1	.75"	Cplg.		6000#	Welded
10. INSPECTION Mant	Noles. No		Size	Location		
OPENINGS Hand			Şire.	Location		
11. SUPPORTS: Skirt_		(Number)	Logs (Number)	Other (Describe	Attached	(Where & How)
12. REMARKS	Fabricat	ed per Tr	inity Drawl	te Tank LPO	Tenk used	in non-corrective serv
	15" Plog	in head -	the vestel, as Alr T	with back up	DRE & 1005 x-	ray.
					e when apply this.	
We certify that the stat	ternents made in th or Pressure Vessels, I	Section VIII, D	errect and that all initializes 1.	details of design, mats	arial, correction, and	Supri menthip this vessel con-
DeteJan, 3	19 19 73 Big	ned Trini	ty Industr	ins, Inc.	- Gray	
Certificate of Authoriza	nion Expire	Janu	ary 7. 1971			The state of the s
VERBEL MADE BY	Trinit	y Industr	ies, Inc.	SHOP INSPECTION Rocky	Mount, N. C.	Sale Sale Sale
I, the undersig State or Province of	North Car North Car	olina	and amployed by	N. C. D	ept. of Labor	Boile rBureau and in this menufacture's
ateta report on	Jan. 30	10 73	, and mate that	to the best of my ke	sectadar and ballet, t	he subschecturer has ear-
By starting thes described in this re	perufficate neither i	he inspector to	or file seratory or more the	the Addition and the second and a second and the second secon	ersessed or breathed, container shall be Methods in any	arming the pressure wanted
and and	and					and the second of the
And Supremented	1000000	- Standing	Calter	man phile	and the star	TAL ANY OR AND
second second second second second second second	Contraction of the local division of the	A REAL PROPERTY AND				