## TRANSTECH ENERGY

## Used 18,000 Gallon Storage Vessel

## Available for Immediate Delivery LPG/NGL Service

## This tank is located in Lugoff, SC

If we do not have a new or used tank or set of matching storage vessels in inventory to suit your needs, we will gladly locate the tanks you need at a competitive price, or we can **custom** manufacture the tank or set of vessels you require—to your exact specifications.

Year	MFG	Capacity	PSI	Serial No.	U1A Data Report
1955	RD Cole	18,000	250	8272	Available



1. Manufactured	by R. D.	COLS HARU	PACTORIN			ATOROAD	and the second second
3 M	Canthan		(Name and a				
A. MARGINECUTED I	or_DOMPHISM	LAFA LOR	(Name and	address of Purchaser)	my - cay	se (coim	apia), 5,0
Herit. or	Art.) (Tank, Jacks	ted. Heat Each.)	o. (	) () (State & State No.) nks), jackets of jack	Nat'l Bd. No	1047 Y.	Built 1955
			Course as air to	Corre	eted vessels, or	shells of Heat	Exchangers
4. SHELL: Materia	(Kind and Spec. N		4 Lowest T.S.)	ness 1 in. Allow	ancein.	Diam. 9. ft. 3 is	. Length 38. 11
5. SEAMS: Long	d. Del., Slaple, Lap.	Butth (Yes	X R. Spet Se	Complete) (	No Efficie Yes er No 3	ncy_80	- fully on re
6. HEADS: (a) Ma	sterial SA-	212	TSFB 700	Spot Sectioned	-212 No. 6	of Courses	T.5 PB 7
(Tep. boltom, es	ede) Thickness	Crown	Knuckie Nadius	Clientical Conica	1 Hemispheric		Side to Pressure (Convex or Concav
(.) _ Ends	1/2*				55=1/2		Conceve
(b)# If removable, be				and the second s			•
	. 0		. T.S., Size, Nemi	Other faste	ning(	Describe or Atta	ch Sketch)
7. STAYBOLTS	If he	llow	Attachment				
8. JACKET CLOS		(Size of Hule)		Threaded, Welded)	(Horiz.)	(Vert.)	(Nominal)
		(Describe a	s oges & weld, be	er, etc. If her give dime	nsions, if bolted, a	describe or skete	h)
9. Constructed for teme 10 and 11 to be	pressure e		i. Max. Temp.	600 'F. Subze	10'F	Hydroetatic T	est
0. TUBE SHEETS:	e completed for t	ubc sections.					
. COR SPRETS:	Stationary. Mater	rial (K	and & Spec. No.)	Diam.	in. Thickness	in. Attachm	ent
行わられ しょうかい 日田	Floating Material	1	10.000	1997 - 19			
	Floating. Material	ck	(ind & Spec. No.)	Diem			
T		CK CK		Diese	in Thickness	in. Attachm	ent
I. TUBES: Material	O.	.D	in. Thickness_	Diase	in Thickness	in. Attachm	ent
1. TUBES: Material diama 12-15 incl. to b	O. Kind & Spec. No.) e completed for i	D	in. Thickness of jacketed ven	Diam inches or gage rela, or channels of h	in Thickness Number	in. Attachm	ent
1. TUBES: Material diama 12-15 incl. to b	O. Kind & Spec. No.) e completed for i	D	in. Thickness of jacketed ven	Diam inches or gage rela, or channels of h	in Thickness Number	in. Attachm	(Streight or U)
1. TUBES: Material diame 12-15 incl. to b 2. SHELL: Material	O. Kind & Spee, No.) a completed for i Kind and Spec. No.	(K nner chambera T.S. ) (Fig. or F. B. &	in. Thickness of jacketed ven Thickness Lowest T. S.)	Diam inchea or gage sela, or channels of h Corrosi an in Allowar	in Thickness Number ent exchangers. onin. Di	in_Attachm Type 	(Struight or U) Longth ft. in Friveted de-
1. TUBES: Material diame 12-15 incl. to b 2. SHELL: Material	O. Kind & Spee, No.) a completed for i Kind and Spec. No.	(K nner chambera T.S. ) (Fig. or F. B. &	in. Thickness of jacketed ven Thickness Lowest T. S.)	Diam inchea or gage sela, or channels of h Corrosi an in Allowar	in Thickness Number ent exchangers. onin. Di	in_Attachm Type 	(Struight or U) Longth ft. in Friveted de-
1. TUBES: Material mma 12-15 incl. to b 2. SHELL: Material (1) 3. SEAMS: Long (Welded,	O. Kind & Spee, No.) a completed for i Kind and Spec. No. Dbl., Single, Lep. 8	(K neer chambers T.S. ) (Fig. or F. B. & S.R. Jutt) (Yes or )	in. Thickness of jacketed ves Thickne Lowest T. S.) X.R. No) (Spot or C	Diam or gage eels, or channels of h Cerrosi an in Allowas Sectioned (Y)	in Thickness Number est exchangers on in Di Efficient	in_Attachm Typ amft:in. cy	(Struight or U) Longth ft. in Friveted de-
1. TUBES: Material imme 12-15 incl. to 5 2. SHELL: Material (1) 3. SEAMS: Long (Weißer, Girth	O Kind & Spec. No.) a completed for i Kind and Spec. No. Dbl., Single, Lep. 5	(K nuer chambora T.S ) (Fig. or F. B. 4 S.R. S.R.	in. Thickness of jacketed van Thicknes Lowest T. S.) X.R. (Spot or C. X.R.	Diam inches or gage sels, or channels of h sectioned in Allowas completes Sectioned Y Sectioned Y	in Thickness Number est exchangers in brein Dis Efficient ar No. of	in_Attachm Type  amft:in_ cy	(Straight or U) Length ft. in If riveted de- fully on ra- verse side of form
1. TUBES: Material teme 12-15 incl. to b 2. SHELL: Material 3. SEAMS: Long (Welded, Girth HEADS (a) Mail Location	O Kind & Spec. No.) s completed for i Kind and Spec. No. Dbl., Single, Lep. E terial. Thickness	(K nuer chambora T.S ) (Fig. or F. B. 4 S.R. S.R.	in. Thickness of jacketed van Thicknes Lowest T. S.) X.R. (Spot or C. X.R.	Diam inchea or gage sela, or channels of h Corrosi an in Allowar	in Thickness Number est exchangers in brein Dis Efficient ar No. of	in_Attachm Typ amft:in. cy	(Straight or U) Length ft. in If riveted de- fully on ra- verse side of form
1. TUBES: Material 1. TUBES: Material 2. SHELL: Material 3. SEAMS: Long (Weidad; Gith 4. HEADS (a) Mai Lossian (a) Top, bottom, et (b) Channel	O Kind & Spec. No.) s completed for i Kind and Spec. No. Dbl., Single, Lep. E terial. Thickness	(K nuer chambora T.S ) (Fig. or F. B. 4 S.R. S.R.	in. Thickness of jacketed van Thicknes Lowest T. S.) X.R. (Spot or C. X.R.	Diam inches or gage sels, or channels of h sectioned in Allowas completes Sectioned Y Sectioned Y	in Thickness Number est exchangers in brein Dis Efficient ar No. of	in_Attachm Type  amft:in_ cy	(Straight or U) Length ft. in If riveted de- cribe seams fully on ra- verse side of form
1. TUBES: Material () gmm 12-15 incl. to b 2. SHELL: Material () 3. SEAMS: Long () 4. HEADS (a) Mat Lorento (a) Top, bettop, et (b) Channel (c) Florthop	O. Kind & Spec. No.) a completed for i Kind and Spec. No. Dbl. Single, Lep. 5 berial. Thickness nds	(K nmer chambers T.S. 5.R. 5.R. T.S. Corrent Radius	in. Thickness of jacksted vers towest 7.8.3 voj X.R. (b) Materia Radius E	Diase inches or gage sels, or channels of k ear in. Allowar Completes Sectioned T.S. Sectioned T.S. Ratio Complete T.S.	in Thickness Number est exchangers in brein Dis Efficient ar No. of	in_Attachm Type  amft:in_ cy	(Straight or U) Length ft. in If riveted de- fully on ra- verse side of form
1. TUBES: Material (f) (imme 12-15 incl. to b) 2. SHELL: Material (f) 3. SEAMS: Long (f) (f) 4. HEADS (a) Mat Lorenta (a) Top, bottog, et (b) Channel (c) Florting	O. Kind & Spec. No.) a completed for i Kind and Spec. No. Dbl. Single, Lep. 5 berial. Thickness nds	(K nmer chambers T.S. 5.R. 5.R. T.S. Corrent Radius	in. Thickness of jacksted vers towest 7.8.3 voj X.R. (b) Materia Radius E	Diase inches or gage sels, or channels of k ear in. Allowar Completes Sectioned T.S. Sectioned T.S. Ratio Complete T.S.	in Thickness	in_Attachm Type  amft:in_ cy	(Streight or U) (Streight or U) Length ft. in Friveted de- trans side of form T.S. Side to Pressure Convex or Concern
1. TUBES: Material (f) (imme 12-15 incl. to b) 2. SHELL: Material (f) 3. SEAMS: Long (f) (f) 4. HEADS (a) Mat Lorenta (a) Top, bottog, et (b) Channel (c) Florting	Kind & Speen Nn.)     0       completed for i     i       Kind and Speen Nn.     i       Dbl. Single, Lap. E     i       Thickness     i       bolks used (a)i     i	(K nmer chambers T.S. 5.R. 5.R. T.S. Corrent Radius	in. Thickness of jacksted vers towest 7.8.3 voj X.R. (b) Materia Radius E	Dian inches or gage orfs, or channels of K sectioned the channels of K sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel section of the channel of the channel section of the channel of the channel section of the channel of the channel of the channel section of the channel of th	in Thickness Number est exchangers, on croin, Di Efficient ts or No? No, of  (c) Mat Hentingberteal Roberts	in Attachm Type am_ft_in. courses erial Flat. Dianaster	(Streight or U) (Streight or U) Length ft interest erifie and des restreight on re- vorse either faith on Preserve Convex or Concern
<ol> <li>TUBES: Material time 12-13 (and to be 2. SHELL, Material 3. SEAMS: Long. (Write</li></ol>	Kind & Susen No.) a completed for i Kind and Spec. No. Dbl. Single, Lap. 5 terial Thickness nds bolks used (a) (c)	(K neer chambers T.S. (Fig. or F. B. 4 S.R. T.S. (Ves or ) S.R. (Material, Spe	in. Thickness_ of jacksted van Thicknes Ezowart 8, 3 (a) (Spot or C X R. (b) Materin Fanddan Raddan E. No. 7.3, Stan	Dian inches or gage orfs, or channels of K sectioned the channels of K sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel section of the channel of the channel section of the channel of the channel section of the channel of the channel of the channel section of the channel of th	in Thickness Number est exchangers, on croin, Di Efficient ts or No? No, of  (c) Mat Hentingberteal Roberts	in Attachm Type am_ft_in. courses erial Flat. Dianaster	(Streight or U) (Streight or U) Length ft interest erifie and des restreight on re- vorse either faith on Preserve Convex or Concern
TURES: Material mme 12-15 lact (to b SHELL: Material SEAMS: Long Girth	Kind & Speen No.) a completed for i Kind and Spee. No. Dbl. Single. Lap. 8 terial Thickness nds (c) (c) (c) (c)	(K nmer chambors T.S. ) (Fig. or F. B. 4 S.R. 	in. Thickness_ of jacketed van Ezowar T. S.J No) (Sport or C X.R. (b) Materia Radius E. No. T.S. Sho.	Dian inches or gage sets, or channeck of k set in. Allowin the Cerronic results set inned T Sectioned T Sectioned T Sectioned Sectio	in Thickness Number net exchangers, nn, Di Efficient ts or Noi No. of No. of No. of No. of No. of Mathematical Hereinglewised JD fastening	in. Attachm Type am_ft_in. courses courses courses inl Danses Danses inl Danses inl Danses courses cou	(Streight or U) (Streight or U) Length_ft_in T.S. T.S. Side of rese side of rese side of rese. Side of Control (Streight or Control (Streight or U) (Streight or U)
<ol> <li>TUBES: Material, anne 12-15 incl. (a b 3. SEAMS: Long. Girth</li></ol>	Kind & Speen No.) a completed for i Kind and Spee. No. Dbl. Single. Lap. 8 terial Thickness nds (c) (c) (c) (c)	(K nmer chambors T.S. ) (Fig. or F. B. 4 S.R. 	in. Thickness_ of jacketed van Ezowar T. S.J No) (Sport or C X.R. (b) Materia Radius E. No. T.S. Sho.	Dian inches or gage orfs, or channels of K sectioned the channels of K sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel sectioned the channel of the channel section of the channel of the channel section of the channel of the channel section of the channel of the channel of the channel section of the channel of th	in Thickness Number net exchangers, nn, Di Efficient ts or Noi No. of No. of No. of No. of No. of Mathematical Hereinglewised JD fastening	in Attachm Type am_ft_in. courses erial Flat. Dianaster	(Streight or U) (Streight or U) Length ft. in T. S. Treated dame trans aide of rese aide of T. S. Side of Control T. S. Side of Control Convert of Control Control Convert of Control Convert of Control Control Convert of Control Convert of Control Convert of Control Convert of Control Co
1. TUBES: Material mme 12-15 incl. (a b 2. SHELL: Material 3. SEANS: Long. Girth	Kind & Juess No.) a completed for i Kind and Spec. No. Did. Single, Lep. 8 terial Thickness nds (c) Jack (pressure of Let. (pressure of Dideted for all Ves	(K D	in. Thickness of Jackoted van Thicknes Lounset 7, 53 (Spot arc X.R. (C) Materia Facilita in. No. 7.3., 54m, (Arc. Temp. (Arc. Temp. (Arc. Temp. (Arc. Temp.))	Dians inches or page orth, or channech of k se in Allowar omplaces Sectioned T S. Sectioned T S. Number (b) Other	in Thickness Number	in_Attachm Typ amftin_ courses_ courses_ courses_ trial Data Data Data Data Data Data Data Da	(Streight or U) (Streight or U) Length ft. in T. S. Treated dame trans aide of rese aide of T. S. Side of Control T. S. Side of Control Convert of Control Control Convert of Control Convert of Control Control Convert of Control Convert of Control Convert of Control Convert of Control Co
<ol> <li>TURES: Material terms 12-15 incl to b terms 12-15 incl to b 2. SHELL: Material (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Ci</li></ol>	Kind & Juess No.) a completed for i Kind and Spec. No. Did. Single, Lep. 8 terial Thickness nds (c) Jack (pressure of Let. (pressure of Dideted for all Ves	(K D	in. Thickness of Jackoted van Thicknes Lounset 7, 53 (Spot arc X.R. (C) Materia Facilita in. No. 7.3., 54m, (Arc. Temp. (Arc. Temp. (Arc. Temp. (Arc. Temp.))	Dians inches or page orth, or channech of k se in Allowar omplaces Sectioned T S. Sectioned T S. Number (b) Other	in Thickness Number net exchangers, nn, Di Efficient ts or Noi No. of No. of No. of No. of No. of Mathematical Hereinglewised JD fastening	in_Attachm Typ amftin_ courses_ courses_ courses_ trial Data Data Data Data Data Data Data Da	(Streight or U) (Streight or U) Length ft. in T. S. Treated dame trans aide of rese aide of T. S. Side of Control T. S. Side of Control Convert of Control Control Convert of Control Convert of Control Control Convert of Control Convert of Control Convert of Control Convert of Control Co
TUBES: Material mme 12-15 incl. (a b mme 12-15 incl. (a b SEANS: Long. Girth	Kind & Speen No., completed for i completed for i Kind and Spec. No. Dbi. Single. Lep. S Dbi. Single. Lep. S drist. Thiskness nds (c)_ fast. foreaure of fast. foreaure of detected for all Ves OUTLETS: Num	(K D)	in Thickness_ of jackstud vice Thicknesser 1, 51 No. X.R. (b) Materia Radian R. No. 73. Stan (b) Materia Radian S. No. 73. Stan S. S. San S. S. San S. S. S. San	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	In Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length ft. in T. S. Treated dame trans aide of rese aide of T. S. Side of Control T. S. Side of Control Convert of Control Control Convert of Control Convert of Control Control Convert of Control Convert of Control Convert of Control Convert of Control Co
<ol> <li>TURES: Material terms 12-15 incl to b terms 12-15 incl to b 2. SHELL: Material (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Ci</li></ol>	Kind & Speen No., completed for i completed for i Kind and Spec. No. Dbi. Single. Lep. S Dbi. Single. Lep. S drist. Thiskness nds (c)_ fast. foreaure of fast. foreaure of detected for all Ves OUTLETS: Num	(K D) meer chambers T.S. (Fig. or P.B. b S.R. S.R. T.S. Norman Redites (Material, Sp. page of the second page	in Thickness_ of jackstud vice Thicknesser 1, 51 No. X.R. (b) Materia Radian R. No. 73. Stan (b) Materia Radian S. No. 73. Stan S. S. San S. S. San S. S. S. San	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	in Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length ft. in T. S. Treated dame trans aide of rese aide of T. S. Side of Control T. S. Side of Control Convert of Control Control Convert of Control Convert of Control Control Convert of Control Convert of Control Convert of Control Convert of Control Co
<ol> <li>TURES: Material terms 12-15 incl to b terms 12-15 incl to b 2. SHELL: Material (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Circh- (Writer, Circh- Ci</li></ol>	Kind & fore, No.1 completed for 1 Kind and Spin. No. Dia. Singh, Lep. B bala used (a) (c) Las. ( preserve all Vec OUTLETS: Num Number 3	(K D)	in Thickness of Jackstud van Lannary S.J. (Spot arc (Spot arc (N Materia) Radius an No. 73. Jan Matine (Geo Temp Salas) (Geo Temp Salas) (Spot arc Salas) (Spot arc (Spot arc (Spot arc)) (Spot arc) (Spot arc) (	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	In Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length ft. min Frijverd de- frijver de- frijver de- frijver de- frijver de- frijver de- frijverd ft.
<ol> <li>TUBES: Material, difference in the second sec</li></ol>	Kind & Seen, No.) completed for 3 Kind and Spin. No. Dial. Singh. Lap. 3 Srial. Thinkness del (c) lat. { preserve al hairs used (c) COTLETS: Num Number 3 3	(K D	in Thickness_ of jackstud vice Thicknesser 1, 51 No. X.R. (b) Materia Radian R. No. 73. Stan (b) Materia Radian S. No. 73. Stan S. S. San S. S. San S. S. S. San	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	In Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length ft. min Frijverd de- frijver de- frijver de- frijver de- frijver de- frijver de- frijverd ft.
TURES: Material TURES: Material SEAMS: Long SEAMS: Long SEAMS: Long Carsh FEADS (a) Mat FEADS (b) Mat Top, barten, er (b) Classial Constructed for Top Seatons Se	Kind & Seer, No completed for No completed for No Kind and Spar. No Dit. Singh, Lep. B bolts used (a) to an even of the second (a) to an even of the second (a) Number Second Second	(K D)	in Thickness of Jackstud van Lannary S.J. (Spot arc (Spot arc (N Materia) Radius an No. 73. Jan (Spot arc (Spot arc) (Spot arc) (Spo	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	In Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length Jt. m. Frieden Streiche seaars friedy on re- frem eide of T.S. Sole of Property Sole of Streiches Sol
TURES: Material TURES: Material The second second SEAMS: Long. Cirth. SEAMS: Long. Girth. SEAMS: Long. Girth. Second second second Constructed for J SAFETY VALVE SAFETY SAFET	Kind & Seen, No.) completed for 3 Kind and Spin. No. Dial. Singh. Lap. 3 Srial. Thinkness del (c) lat. { preserve al hairs used (c) COTLETS: Num Number 3 3	(K D	in Thickness of Jackstud van Lannary S.J. (Spot arc (Spot arc (N Materia) Radius an No. 73. Jan (Spot arc (Spot arc) (Spot arc) (Spo	Dian inches or gage or gage seth, ur channels of 1 cervair seth, and cervair seth, and cervair sether (Y) Sectioned (Y) (Y) (Y) (Y) (Y) (Y) (Y) (Y)	In Thickness Number	in_Attacham Typp 	(Streight or U) (Streight or U) Length Jt. m. Frieden Streiche seaars friedy on re- frem eide of T.S. Sole of Property Sole of Streiches Sol
TURES: Material diame 12-15 lact to diameter di diameter diameter diameter diameter	Kind & Seen, No.) completed for a kind and Spec. No. brink and Spec. No. Dial, Singh, Lap, S arial. Thukness bolts used (a). (c). Lat. (preserve al bolts used (a). (c). Lat. (preserve al bolts used (a). (c). Lat. (preserve al bolts used (b). (c). Lat. (preserve al bolts used (b). (c).	(K D	in Thickness of Jackstud van Lannary S.J. (Spot arc (Spot arc (N Materia) Radius an No. 73. Jan (Spot arc (Spot arc) (Spot arc) (Spo	Dian inches or gege orte, or channels of the Cerroni sectioned in Allowat Sectioned Ty Sectioned Ty Sectioned (b) Other Variant Super- Sectioned Ty Super- sectioned Ty Other Super- sectioned Ty Other Decesion Location	in Thickness	in Attachm Typ annftin courses_ courses_ courses courses_ courses	(Streight or U) (Streight or U) Length It. min (Streich seams fully an re- frem mide of T.S. Bake of Property T.S. Bake of Property T.S. Bake of Property Field of S
TURES: Material TURES: Material SEANS: Long SEANS: Long Circh Girch Teation (a) Top: barten Teation (b) Classial Termovikle, Termovikle, Termovikle, Constructed for Toperation SAFETY Value NORECTION M OFENINGS: N SUPPORTS: Skirt.	Kind & Seer, No. 1 completed for No. 1 completed for No. 1 Kind and Spar. No. 1 Dia, Singha, Lap, B balls used (a)	(K D	in Thickness of Jackstud van Lannary S.J. (Spot arc (Spot arc (N Materia) Radius an No. 73. Jan (Spot arc (Spot arc) (Spot arc) (Spo	Dian inches or gege orte, or channels of the Cerroni sectioned in Allowat Sectioned Ty Sectioned Ty Sectioned (b) Other Variant Super- Sectioned Ty Super- sectioned Ty Other Super- sectioned Ty Other Decesion Location	In Thickness Number	in Attachm Typ annftin courses_ courses_ courses courses_ courses	(Streight or U) (Streight or U) Length Jt. m. Frieden Streiche seaars friedy on re- frem eide of T.S. Sole of Property Sole of Streiches Sol



**Need help with your project?** Save time and money, TransTech can provide Valve & Instrumentation kit to fit your tank, freight to the project site and full installation. Feel comfortable

your project will be installed to the latest NFPA 58 Standard and will fit your needs.

**Tank Set & Installation!** From providing expert engineering assistance in specifying the correct valve and instrumentation, size piers to coordination of freight and offloading - through to site excavation and tank set, we provide a turnkey

bulk plant or terminal solution.



TransTech Energy LLC - Tel: (+1)888-206-4563 www.transtechenergy.com